



Oxylub[®]-327

glass forging lubricant for titanium alloys

Description

A water-based, protective and lubricating glass coating formulated to protect from hydrogen penetration and lubricate titanium alloys during hot forging processes.

Performance Characteristics

- effective temperature range 1500-1875^o F (815-1024^o C)
- provides excellent lubrication during forging and extrusion
- retards hydrogen penetration and protection against alpha case development
- exceptional insulating properties and thermal stability
- demonstrates heat retention properties for improved performance in hot working operations
- outstanding coverage & performance in one coat
- demonstrates exceptional green strength upon proper drying to withstand cracking, chipping, and peeling
- provides excellent rheological properties for dipping and spaying applications
- coating can be diluted with water to obtain desired spray viscosity – do not over-thin coating

Recommendations for Use

- thoroughly suspend and mix before use
- metal surfaces must be free of dirt, oil, grease, metal oxides, and other materials
- coating thickness depends on the time and temperature of exposure (generally, the higher the temperature and longer exposure, the thicker the coating should be applied)
- a wet film thickness of 5 ± 2 mils should be optimal
- ensure bottom coat is thoroughly dried when applying multiple coats
- water-based coatings need ample time to completely dry before entering furnace (can be applied over preheated substrate to accelerate drying time)

Typical Properties

pH	6.0-7.0
% Solids	52.0-56.0
Vehicle	Water
Viscosity (@ 25°C) as Supplied (cP)	1,200-1,400
Weight/Gallon (lb/gal)	11.85 ± 0.25
Specific Gravity	1.39-1.45

Color	White
Shelf Life	~1 year

Product Safety

Before handling the materials listed in this bulletin, read and understand the product MSDS (Material Safety Data Sheet) for additional information on personal protective equipment and for safety, health, and environmental information.

No chemical should be used as or in a food, drug, medical device, or cosmetic, or in a product or process in which it may contact a food, drug, medical device, or cosmetic until the user has determined the suitability and legality of the use. Since government regulations and use conditions are subject to change, it is the user’s responsibility to determine that this information is appropriate and suitable under current, applicable laws and regulations.

Advanced Technical Products Supply Co., Inc. requests that the customer read, understand, and comply with the information contained in this publication and the current SDS(s). The customer should furnish the information in this publication to its employees, contractors, and customers, or any other users of the product(s), and request that they do the same.

Storage and Handling

Oxylub®-327 should be stored indoors in the original unopened and undamaged container, in a dry place at a temperature not exceeding (40° C). Exposure to direct sunlight should be avoided.

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Advanced Technical Products expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated any may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.



Advanced Technical Products Supply Co., Inc.
 6186 Centre Park Drive
 West Chester, OH 45069
 USA

Telephone: 1.513.851.6858 Facsimile: 1.513.851.6824

info@advancedtechnicalprod.com

Visit our website:
 www.advancedtechnicalprod.com

